




Avocent AVO-150LN-24W Specifications

Light Source	LED SMD2835	Supply (Voltage)	220-240V AC~50/60Hz
Colours	Ash with White, Black Ash with Black, Walnut with Black	Temperature Rating	-20°C +25°C
Wattage	24W	Construction	Ash Wood & Aluminium
Kelvins	3000K - 4000K - 6000K	IP Rating	IP20
Lumens	1166lm - 1262lm - 1201lm	Electrical Protection	Class II
CRI	CRI≥80	Compliance	AS/NZS 60598.1, AS/NZS 60598.2.1, AS/NZS CISPR 15
LED Hour Rating	17650h L80	Recommended Use Warranty	Domestic / Commercial 3 Year Replacement
Beam Angle	120°	NZ/AU Driver Driver Type	LF-GIF040YS080H Constant C, Isolated
		Net Weight Gross Weight	3.5KG 4.5KG


All fixtures must be installed by a licensed electrician. Please also consult a licensed electrician for any electrical and wiring enquiries. For technical support please contact: customerservice@calibo.com.au

Also available in other configurations



[VIEW RANGE PAGE](#)





Avocent AVO-200LN-32W Specifications

Light Source	LED SMD2835	Supply (Voltage)	220-240V AC~50/60Hz
Colours	Ash with White, Black Ash with Black, Walnut with Black	Temperature Rating	-20°C +25°C
Wattage	32W	Construction	Ash Wood & Aluminium
Kelvins	3000K - 4000K - 6000K	IP Rating	IP20
Lumens	1696lm - 1755lm - 1565lm	Electrical Protection	Class II
CRI	CRI≥80	Compliance	AS/NZS 60598.1, AS/NZS 60598.2.1, AS/NZS CISPR 15
LED Hour Rating	17650h L80	Recommended Use Warranty	Domestic / Commercial 3 Year Replacement
Beam Angle	120°	NZ/AU Driver Driver Type	LF-GIF040YS080H Constant C, Isolated
		Net Weight Gross Weight	4.5KG 5.5KG

All fixtures must be installed by a licensed electrician. Please also consult a licensed electrician for any electrical and wiring enquiries. For technical support please contact: customerservice@calibo.com.au

Also available in other configurations



[VIEW RANGE PAGE](#)

